NSN 5962-01-067-3069

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-067-3069 **Body Length:** Between 0.365 inches and 0.385 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.070 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** +0.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and hybrid and negative outputs and positive outputs **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 1 amplifier, hybrid and 1 buffer **Terminal Surface Treatment:** Gold **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 53711-5165635 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig: A458a0