NSN 5962-01-067-4982



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-067-4982 **Body Length:** 2.080 inches **Body Width:** Between 0.510 inches and 0.615 inches **Body Height:** Between 0.165 inches and 0.205 inches **Maximum Power Dissipation Rating:** 1.7 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and negative outputs and 3-state output and w/buffered output and resettable and w/enable and edge triggered and w/storage **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 18 input **Design Function And Quantity:** 1 microprocessor **Case Outline Source And Designator:** Q-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

40 printed circuit

Specification Data:

81349-mil-m-38510/420 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Ves - demil/mli

NSN 5962-01-067-4982

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0