## NSN 5962-01-067-4983

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5062-01-067-4083

view Online at https://aerobasegroup.com/hsn/5962-01-067-4963
Body Length:
Between 0.810 inches and 0.870 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Multiplexer type td-1269/g
Features Provided:
Asynchronous and monolithic and positive outputs and programmable and w/enable and dual edge triggered and presettable and
synchronous
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
9 input
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.5 volts power source
Time Rating Per Chacteristic:
1100.00 nanoseconds propagation delay time, low to high level output and 1100.00 nanoseconds propagation delay time, high to low lev
output
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Ves - demil/mli

Fiig:

A458a0