## NSN 5962-01-067-4984



Memory Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-067-4984 **Body Length:** Between 1.490 inches and 1.510 inches **Body Width:** Between 0.565 inches and 0.590 inches **Body Height:** 0.200 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **End Application:** Multiplexer type td-1269/g **Features Provided:** Monolithic and hermetically sealed and w/buffered output and w/enable and resettable and w/storage and negative outputs and positive outputs **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** P-type metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 0.3 volts power source **Time Rating Per Chacteristic:** 600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** First-in first-out **Memory Capacity:** 

Unknown

**Terminal Type And Quantity:** 

28 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0