# NSN 5962-01-067-8315

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-067-8315

# **Body Length:**

Between 0.660 inches and 0.785 inches

# **Body Width:**

Between 0.220 inches and 0.280 inches

# **Body Height:**

Between 0.140 inches and 0.180 inches

# **Maximum Power Dissipation Rating:**

303.0 milliwatts

#### **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### End Application:

Radar set type an/fps-115

### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and medium power and medium speed and w/disable and 3-state output

### Inclosure Material:

Plastic

### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Quad 2 input

# **Design Function And Quantity:**

4 buffer, inverting

# Case Outline Source And Designator:

T0-116 joint electron device engineering council

# **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

5.5 volts power source

# **Time Rating Per Chacteristic:**

16.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

04761-640-200063 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Terminal Type And Quantity:**

14 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5962-01-067-8315

Digital Microcircuit - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0

