

View Online at <https://aerobasegroup.com/nsn/5962-01-068-1047>

Body Length:

Between 0.750 inches and 0.785 inches

Body Width:

Between 0.240 inches and 0.295 inches

Body Height:

Between 0.160 inches and 0.180 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-40.0/+85.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Receiver, radio type r-2130/grr

Features Provided:

Hermetically sealed and monolithic and positive outputs and low power and w/enable and resettable and presettable and asynchronous and synchronous

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

1 counter, binary coded decimal up/down

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

18.5 volts power source

Time Rating Per Characteristic:

1100.00 nanoseconds propagation delay time, low to high level output and 1100.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0