## NSN 5962-01-068-2623

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-068-2623

| Body Length:   |
|--|
| 1.300 inches   |
| Body Width:  |
| 1.300 inches   |
| Body Height:   |
| 0.230 inches   |
| Maximum Power Dissipation Rating:  |
| 125.0 milliwatts   |
| Operating Tempurature Range:   |
| -46.0/+86.0 degrees celsius  |
| Storage Tempurature Range:   |
| -65.0/+165.0 degrees celsius   |
| End Application:   |
| 5820-01-027-9071   |
| Features Provided:   |
| Hermetically sealed and hybrid and negative outputs and positive outputs   |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Input Circuit Pattern:   |
| 14 input   |
| Design Function And Quantity:  |
| 1 filter, active   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 12.0 volts power source  |
| Time Rating Per Chacteristic:  |
| 125.00 nanoseconds propagation delay time, low to high level output  |
| Test Data Document:  |
| 87990-755002a7710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                      |
| Terminal Type And Quantity:  |
| 25 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |

A458a0