## NSN 5962-01-068-2632

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-068-2632

view Online at https://aerobasegroup.com/nsn/5962-01-066-2652
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
170.0 milliwatts
Operating Tempurature Range:
+0.0/+75.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and expandable
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Diode-transistor logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 gate, nand
Case Outline Source And Designator:
T0.116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
8.0 volts power source
Time Rating Per Chacteristic:
35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Vas - demil/mli

Fiig:

A458a0