

View Online at <https://aerobasegroup.com/nsn/5962-01-068-2643>

**Body Length:**

Between 0.370 inches and 0.400 inches

**Body Width:**

Between 0.245 inches and 0.260 inches

**Body Height:**

Between 0.060 inches and 0.080 inches

**Maximum Power Dissipation Rating:**

760.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+175.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and negative outputs and high speed and schottky and w/totem pole output

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Emitter-coupled logic

**Input Circuit Pattern:**

Quad 2 input

**Design Function And Quantity:**

4 translator, level

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-8.0 volts power source

**Time Rating Per Characteristic:**

8.00 nanoseconds propagation delay time, low to high level output and 8.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

82577-932665 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0