NSN 5962-01-068-7840

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-068-7840

/lew Online at https://aerobasegroup.com/nsn/5962-01-066-7640
Body Length:
Between 1.188 inches and 1.290 inches
Body Width:
Between 0.515 inches and 0.590 inches
Body Height:
Between 0.100 inches and 1.160 inches
Maximum Power Dissipation Rating:
550.0 milliwatts
Operating Tempurature Range:
-0.0/+70.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/enable and high speed and schottky and 3-state output
nclosure Material:
Ceramic and glass
nclosure Configuration:
Dual-in-line
Output Logic Form:
Fransistor-transistor logic
nput Circuit Pattern:
3 input
Ferminal Surface Treatment:
Solder
/oltage Rating And Type Per Characteristic:
5.5 volts power source
Fime Rating Per Chacteristic:
70.00 nanoseconds propagation delay time, low to high level output and 70.00 nanoseconds propagation delay time, high to low level
putput
Memory Device Type:
Rom
Memory Capacity:
Jnknown
Test Data Document:
3499-638-2213 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Ferminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-068-7840

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0