NSN 5962-01-069-0409

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-069-0409

Body Length:
Between 0.770 inches and 0.810 inches
Body Width:
Between 0.280 inches and 0.300 inches
Body Height:
Between 0.060 inches and 0.120 inches
Maximum Power Dissipation Rating:
450.0 milliwatts
Operating Tempurature Range:
-25.0/+85.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Receiver, radio type r-2130/grr
Features Provided:
Hermetically sealed and monolithic and negative outputs and positive outputs and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
11 input
Design Function And Quantity:
2 multiplexer, analog
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
17.0 volts power source
Time Rating Per Chacteristic:
800.00 nanoseconds propagation delay time, low to high level output and 800.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0