NSN 5962-01-069-6803

Linear Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-069-6803 **Body Length:** Between 0.355 inches and 0.390 inches **Body Width:** Between 0.240 inches and 0.275 inches **Body Height:** 0.080 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hybrid and negative outputs and positive outputs and hermetically sealed **Inclosure Material:** Glass and metal **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 7 input **Design Function And Quantity:** 1 switch, analog **Terminal Surface Treatment:** Solder **Time Rating Per Chacteristic:** 450.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 06481-970304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli