## NSN 5962-01-069-9735

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-069-9735

## **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.120 inches and 0.185 inches **Maximum Power Dissipation Rating:** 54.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs **Inclosure Material:** Silicon **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Emitter-coupled logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 gate, or-nor **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 10.0 volts power source **Time Rating Per Chacteristic:** 7.50 nanoseconds propagation delay time, low to high level output and 7.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 97942-581r642 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a Unit Of Measure: --**Demilitarization:** Yes - demil/mli Fiig: A458a0