## NSN 5962-01-069-9737

Digital Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-069-9737

Body Length:
0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.120 inches and 0.185 inches
Maximum Power Dissipation Rating:
26.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and negative outputs
Inclosure Material:
Silicon
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Emitter-coupled logic
Input Circuit Pattern:
Triple 3 input
Design Function And Quantity:
3 gate, nor
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Time Rating Per Chacteristic:
7.00 nanoseconds propagation delay time, low to high level output and 7.50 nanoseconds propagation delay time, high to low level output
Test Data Document:
97942-581r641 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig: