NSN 5962-01-070-8976

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-070-8976

Body Length:	
0.440 inches	
Body Width:	
Between 0.245 inches and 0.285 inches	
Body Height:	
Between 0.045 inches and 0.085 inches	
Maximum Power Dissipation Rating:	
692.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and monolithic and positive outputs and edge triggered and schottky and w/clear and w/enable	
Inclosure Material:	
Ceramic and glass	
Inclosure Configuration:	
Flat pack	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
8 input	
Design Function And Quantity:	
6 flip-flop, d-type	
Case Outline Source And Designator:	
F-5 mil-m-38510	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
5.5 volts power source	
Test Data Document:	
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in sp	ecification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cer	rtain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
16 flat leads	
Specification Data:	
81349-mil-m-38510/71 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	

NSN 5962-01-070-8976

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

