## NSN 5962-01-070-8977

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5062-01-070-8077

View Online at https://aerobasegroup.com/nsn/5962-01-070-8977
Body Length:
0.440 inches
Body Width:
Between 0.245 inches and 0.285 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
336.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and schottky and w/enable and w/strobe and w/buffered output
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
4 multiplexer, two to one line
Case Outline Source And Designator:
F-5 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Special Features:
Inverted output
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
16 flat leads
Specification Data:
81349-mil-m-38510/79 government specification

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5962-01-070-8977

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0