NSN 5962-01-071-1795

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-071-1795

Body Dutside Diameter: Between 0.335 inches and 0.370 inches Body Height: Between 0.240 inches and 0.260 inches Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: +0.0/+70.0 degrees celsius Features Provided: Monolibitic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0.002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 50.000 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure:	
Body Height: Between 0.240 inches and 0.260 inches Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifler, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demili/mil Fiig:	Body Outside Diameter:
Between 0,240 inches and 0.260 inches Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli Fitig:	Between 0.335 inches and 0.370 inches
Operating Tempurature Range: +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: Vua Unit Of Measure: Demilitarization: Yes - demil/mli Filig:	Body Height:
+0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fitig:	Between 0.240 inches and 0.260 inches
Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 ampliffer, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Operating Tempurature Range:
-65.0/+150.0 degrees celsius Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 ampliffer, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Filg:	+0.0/+70.0 degrees celsius
Features Provided: Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Storage Tempurature Range:
Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	-65.0/+150.0 degrees celsius
Inclosure Material: Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Features Provided:
Glass and metal Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Monolithic and hermetically sealed and negative outputs and positive outputs and externally compensated and high speed
Inclosure Configuration: Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fitig:	Inclosure Material:
Can Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fitig:	Glass and metal
Input Circuit Pattern: 3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Inclosure Configuration:
3 input Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Can
Design Function And Quantity: 1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Input Circuit Pattern:
1 amplifier, operational, general purpose Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	3 input
Case Outline Source And Designator: -0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Design Function And Quantity:
-0-002-aa joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	1 amplifier, operational, general purpose
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Case Outline Source And Designator:
Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	-0-002-aa joint electron device engineering council
Voltage Rating And Type Per Characteristic: 15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Surface Treatment:
15.0 volts power source Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Solder
Time Rating Per Chacteristic: 500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Voltage Rating And Type Per Characteristic:
500.00 nanoseconds propagation delay time, low to high level output Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	15.0 volts power source
Terminal Type And Quantity: 8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Time Rating Per Chacteristic:
8 pin Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	500.00 nanoseconds propagation delay time, low to high level output
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	8 pin
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:
Demilitarization: Yes - demil/mli Fiig:	N/a
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	Demilitarization:
	Yes - demil/mli
A458a0	Fiig:
	A458a0