## NSN 5962-01-071-3707

Digital Microcircuit - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5962-01-071-3707
Body Length:
Between 0.240 inches and 0.275 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.030 inches and 0.070 inches
Maximum Power Dissipation Rating:
60.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5895-00-197-9925 communication central
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/enable and negative edge triggered and medium speed and resettable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
1 flip-flop, j-k, or input
Case Outline Source And Designator:
T0-85 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

## NSN 5962-01-071-3707

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0