NSN 5962-01-071-3707

Digital Microcircuit - Page 1 of 2



| view Online at https://aerobasegroup.com/hsn/5962-01-071-3707 |
|----------------------------------------------------------------------------------------------------------------------------------|
| Body Length: |
| Between 0.240 inches and 0.275 inches |
| Body Width: |
| Between 0.240 inches and 0.260 inches |
| Body Height: |
| Between 0.030 inches and 0.070 inches |
| Maximum Power Dissipation Rating: |
| 60.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 5895-00-197-9925 communication central |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and w/enable and negative edge triggered and medium speed and resettable |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 10 input |
| Design Function And Quantity: |
| 1 flip-flop, j-k, or input |
| Case Outline Source And Designator: |
| T0-85 joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 14 flat leads |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

Yes - demil/mli

NSN 5962-01-071-3707

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0