NSN 5962-01-071-5331

Memory Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-071-5331 |
|--|
| Body Length: |
| Between 1.200 inches and 1.300 inches |
| Body Width: |
| Between 0.500 inches and 0.600 inches |
| Body Height: |
| 0.200 inches |
| Maximum Power Dissipation Rating: |
| 800.0 milliwatts |
| Operating Tempurature Range: |
| -25.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+125.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and positive outputs and w/storage and programmable and programmed and w/buffered output and |
| w/decoded output and 3-state output |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| N-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 10 input |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 15.0 volts power source |
| Time Rating Per Chacteristic: |
| 2000.00 nanoseconds propagation delay time, low to high level output and 2000.00 nanoseconds propagation delay time, high to low level |
| output |
| Memory Device Type: |
| Rom |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 24 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

Yes - demil/mli

Fiig:

A458a0