NSN 5962-01-072-4080

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-072-4080 **Body Length:** 0.290 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.030 inches and 0.085 inches **Maximum Power Dissipation Rating:** 670.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and positive outputs and w/field effect transistor switch and w/buffered output and bipolar and high voltage **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 amplifier, wideband **Case Outline Source And Designator:** F-4 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 20.0 volts power source **Time Rating Per Chacteristic:** 1500.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 82577-932869 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 10 flat leads Shelf Life: N/a **Unit Of Measure:**

Fiig:

A458a0

Demilitarization: Yes - demil/mli