NSN 5962-01-072-4084

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-072-4084

Body Length:
Between 0.745 inches and 0.755 inches
Body Width:
Between 0.370 inches and 0.380 inches
Body Height:
Between 0.115 inches and 0.125 inches
Maximum Power Dissipation Rating:
450.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hybrid and hermetically sealed and negative outputs and positive outputs and w/enable
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
4 channel
Design Function And Quantity:
1 converter, digital to analog
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Time Rating Per Chacteristic:
1000.00 nanoseconds propagation delay time, low to high level output
Test Data Document:
82577-934316 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
26 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0