## NSN 5962-01-073-4508

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5962-01-073-4508

View Online at https://aerobasegroup.com/nsn/5962-01-073-4508
Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Range finder, target designator, laser, type an/avq-25
Features Provided:
Hermetically sealed and monolithic and positive outputs and low power and w/enable and resettable and edge triggered and negative edge
triggered
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 counter, binary
Case Outline Source And Designator:
D-2 mil-m-38510
Current Rating Per Characteristic:
100.00 microamperes supply
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
20.0 volts total supply
Test Data Document:
14933-77023 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 printed circuit

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5962-01-073-4508

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0