NSN 5962-01-073-6938

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-073-6938 **Body Length:** 0.730 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** Between 0.150 inches and 0.165 inches **Maximum Power Dissipation Rating:** 900.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 4 channel **Design Function And Quantity:** 4 switch, analog **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 15.0 volts power source **Time Rating Per Chacteristic:** 90.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Yes - demil/mli

Fiig:

A458a0