# NSN 5962-01-073-9544

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-073-9544

#### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

#### **Body Height:**

Between 0.165 inches and 0.185 inches

### **Maximum Power Dissipation Rating:**

600.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and hybrid and positive outputs and negative outputs

#### **Inclosure Material:**

Glass and metal

#### **Inclosure Configuration:**

# Can

**Input Circuit Pattern:** 

1 input

#### **Design Function And Quantity:**

1 amplifier, current

#### **Case Outline Source And Designator:**

To-99 joint electron device engineering council

#### **Terminal Surface Treatment:**

Gold

#### Voltage Rating And Type Per Characteristic:

22.0 volts power source

#### **Time Rating Per Chacteristic:**

12.00 nanoseconds propagation delay time, low to high level output

#### **Precious Material And Location:**

Terminal surfaces gold

#### **Precious Material:**

Gold

## **Test Data Document:**

14933-78013 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

8 pin

Shelf Life:

N/a

#### Unit Of Measure:

- ---
- **Demilitarization:**
- Yes demil/mli

# NSN 5962-01-073-9544

Linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

