

View Online at <https://aerobasegroup.com/nsn/5962-01-074-1655>

Maximum Power Dissipation Rating:

725.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

TEST-SE-T,R-OCKE

Features Provided:

Burn in, mil-std-883, class b and erasable

Inclosure Configuration:

Dual-in-line

Design Function And Quantity:

1 multiplexer, analog

Case Outline Source And Designator:

D-2 mil-m-38510

Current Rating Per Characteristic:

0.50 milliamperes collector cutoff current, dc, with specified resistance between base and emitter blank and 2.00 milliamperes reverse current, dc blank

Product Name:

Microcircuit, 8 channel analog multiplexer

Voltage Rating And Type Per Characteristic:

4.0 volts high input threshold

Capitance Rating Per Characteristic:

25.00 output pascal industrial factory select

Time Rating Per Chacteristic:

0.50 nanoseconds access and 1.00 nanoseconds access

Special Features:

8 channel

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0