NSN 5962-01-074-1789

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-074-1789

View Online at https://aerobasegroup.com/nsn/5962-01-074-1789
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
40.0 milliwatts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
Radar set, type an/fps-115
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/open collector and medium speed
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Quad 2 input
Design Function And Quantity:
4 gate, nand
Case Outline Source And Designator:
T0-116 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
45.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
34010-15104200 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

N/a

Unit Of Measure:

14 printed circuit

Shelf Life:

NSN 5962-01-074-1789

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0