## NSN 5962-01-074-1809

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-074-1809

Body Length:	
0.440 inches	
Body Width:	
Between 0.245 inc	hes and 0.285 inches
Body Height:	
Between 0.045 inc	hes and 0.085 inches
Maximum Power	Dissipation Rating:
545.0 milliwatts	
Operating Tempu	irature Range:
-55.0/+125.0 degre	ees celsius
Storage Tempura	ture Range:
-65.0/+150.0 degre	ees celsius
Features Provide	d:
Hermetically seale	d and monolithic and positive outputs and schottky and 3-state output
Inclosure Materia	I:
Ceramic and glass	
Inclosure Config	uration:
Flat pack	
Output Logic For	m:
Transistor-transist	or logic
Input Circuit Patt	ern:
10 input	
Design Function	And Quantity:
1 multiplexer and	I selector, data
Case Outline Sou	rce And Designator:
F-5 mil-m-38510	
Terminal Surface	Treatment:
Solder	
Voltage Rating A	nd Type Per Characteristic:
5.5 volts power so	burce
Time Rating Per	Chacteristic:
22.00 nanosecond	s propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level
output	
Test Data Docum	ent:
82577-932690 dra	wing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any spec	ification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type Ar	nd Quantity:
16 flat leads	
Shelf Life:	
N/a	
Unit Of Measure:	

**Demilitarization:** Yes - demil/mli

## NSN 5962-01-074-1809

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

