NSN 5962-01-074-3404

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-074-3404
Body Length:
Between 1.543 inches and 1.573 inches
Body Width:
Between 1.030 inches and 1.050 inches
Body Height:
Between 0.250 inches and 0.450 inches
Maximum Power Dissipation Rating:
63.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Set, teletypewriter, type an/ugc-129
Features Provided:
Hermetically sealed and high current and high voltage and hybrid and positive outputs
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Design Function And Quantity:
1 regulator, current
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
60.0 volts power source
Time Rating Per Chacteristic:
150.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
19397-st67268 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli