NSN 5962-01-074-3407

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-074-3407

Body Length: 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and expandable and low power **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 11 input **Design Function And Quantity:** 1 comparator, magnitude **Case Outline Source And Designator:** D-2 mil-m-38510 **Current Rating Per Characteristic:** 10.00 milliamperes supply **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Capitance Rating Per Characteristic:** 7.50 input picofarads **Time Rating Per Chacteristic:** 750.00 nanoseconds delay **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life:

N/a

NSN 5962-01-074-3407

Digital Microcircuit - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

