

View Online at <https://aerobasegroup.com/nsn/5962-01-074-8857>

**Body Length:**

Between 0.240 inches and 0.275 inches

**Body Width:**

Between 0.240 inches and 0.260 inches

**Body Height:**

Between 0.030 inches and 0.070 inches

**Maximum Power Dissipation Rating:**

750.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Guidance unit, midcourse, type cp-1137/dsq-28

**Features Provided:**

Hermetically sealed and hybrid and negative outputs and positive outputs and w/field effect transistor switch

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Input Circuit Pattern:**

Dual 2 input

**Design Function And Quantity:**

2 driver, switch, field effect transistor

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

22.0 volts power source

**Time Rating Per Characteristic:**

130.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output

**Terminal Type And Quantity:**

14 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0