NSN 5962-01-074-8858

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-074-8858

| view Online at https://aerobasegroup.com/hsh/5962-01-074-6656 |
|---|
| Body Length: |
| Between 1.430 inches and 1.450 inches |
| Body Width: |
| Between 0.530 inches and 0.550 inches |
| Body Height: |
| Between 0.095 inches and 0.115 inches |
| Maximum Power Dissipation Rating: |
| 1200.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Guidance unit, midcourse, type cp-1137/dsq-28 |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 16 channel |
| Design Function And Quantity: |
| 1 multiplexer, analog |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 20.0 volts power source |
| Test Data Document: |
| 30003-642as7920 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 28 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig:

A458a0