## NSN 5962-01-074-8871

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-074-8871
Body Length:
0.440 inches
Body Width:
Between 0.245 inches and 0.285 inches
Body Height:
Between 0.045 inches and 0.085 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and edge triggered and medium power and medium speed and w/enable and
schottky
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 3 input
Design Function And Quantity:
2 decoder, two to four line
Case Outline Source And Designator:
F-5 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
17.00 nanoseconds propagation delay time, low to high level output and 17.00 nanoseconds propagation delay time, high to low level
output
Special Features:
Nuclear hardness critical items
Nuclear Hardness Critical Feature:
Hardened
Test Data Document:
82577-932685 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Unit Of Measure:

16 flat leads

Shelf Life:

N/a

**Terminal Type And Quantity:** 

## NSN 5962-01-074-8871

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0