

View Online at <https://aerobasegroup.com/nsn/5962-01-074-8873>

**Overall Height:**

Between 0.050 inches and 0.080 inches

**Body Length:**

Between 0.371 inches and 0.400 inches

**Body Width:**

Between 0.247 inches and 0.285 inches

**Maximum Power Dissipation Rating:**

275.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and complementary outputs and edge triggered and medium power and medium speed and w/enable and w/totem pole output and 3-state output and schottky and true/complementary

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

12 input

**Design Function And Quantity:**

1 multiplexer, one to eight line

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

8.00 nanoseconds propagation delay time, low to high level output and 8.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

82577-932686 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0