NSN 5962-01-075-6886

Memory Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-075-6886 |
|--|
| Body Length: |
| Between 0.850 inches and 0.930 inches |
| Body Width: |
| Between 0.240 inches and 0.295 inches |
| Body Height: |
| Between 0.160 inches and 0.180 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Electrostatic sensitive and hermetically sealed and monolithic and positive outputs and high speed and bipolar and programmed and |
| w/decoded output and 3-state output |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 12 input |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 85.00 nanoseconds propagation delay time, low to high level output and 85.00 nanoseconds propagation delay time, high to low level |
| output |
| Memory Device Type: |
| Rom |
| Memory Capacity: |
| Unknown |
| Test Data Document: |
| 82577-932883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 18 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

A458a0

Yes - demil/mli