Digital Microcircuit - Page 1 of 2

--



View Online at https://aerobasegroup.com/nsn/5962-01-075-7599

Body Length:	
0.380 inches	
Body Width:	
0.200 inches	
Body Height:	
0.075 inches	
Operating Tempura	ture Range:
-55.0/+150.0 degree	s celsius
Storage Tempuratu	re Range:
-65.0/+150.0 degree	s celsius
End Application:	
Guidance unit, midco	purse, type cp-1137/dsq-28
Features Provided:	
Hermetically sealed	and monolithic and w/switch and positive outputs
Inclosure Material:	
Ceramic and glass	
Inclosure Configura	ition:
Flat pack	
Output Logic Form	
Transistor-transistor	logic
Input Circuit Patter	1:
Triple 3 input	
Design Function Ar	Id Quantity:
3 gate, nand	
Terminal Surface T	reatment:
Gold	
Voltage Rating And	Type Per Characteristic:
5.5 volts power sour	ce
Time Rating Per Ch	acteristic:
10.00 nanoseconds	propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level
output	
Precious Material A	nd Location:
Terminal surfaces go	ld
Precious Material:	
Gold	
Test Data Documer	t:
30003-642as7894 dr	awing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any s	pecification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And	Quantity:
14 flat leads	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5962-01-075-7599

Digital Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

