

View Online at <https://aerobasegroup.com/nsn/5962-01-075-9213>

Body Length:

Between 0.371 inches and 0.400 inches

Body Width:

Between 0.247 inches and 0.283 inches

Body Height:

Between 0.050 inches and 0.080 inches

Maximum Power Dissipation Rating:

570.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Guidance unit, midcourse, type cp-1137/dsq-28

Features Provided:

Hermetically sealed and monolithic and positive outputs and w/strobe

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

Dual 5 input

Design Function And Quantity:

2 receiver, line differential

Terminal Surface Treatment:

Gold

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

30003-642as7904 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0