# NSN 5962-01-076-5381

Linear Microcircuit - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5962-01-076-5381

## **Body Length:**

0.185 inches

# **Body Outside Diameter:**

0.370 inches

# **Maximum Power Dissipation Rating:**

220.0 milliwatts

# **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

# **Features Provided:**

High voltage and hermetically sealed and burn in and w/resistor

#### **Inclosure Material:**

Metal

#### **Inclosure Configuration:**

# Can

**Input Circuit Pattern:** 

2 input

# **Design Function And Quantity:**

1 amplifier, operational, general purpose

# **Current Rating Per Characteristic:**

4.50 milliamperes reverse current, dc absolute

# **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

40.0 volts power source

#### **Time Rating Per Chacteristic:**

120.00 nanoseconds delay

#### **Test Data Document:**

03640-6086278 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# **Terminal Type And Quantity:**

8 pin

Shelf Life:

N/a

#### Unit Of Measure:

---

# **Demilitarization:**

Yes - demil/mli

# Fiig:

A458a0

