NSN 5962-01-076-7972

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-076-7972

| Body Length: | |
|--|-------------|
| 0.440 inches | |
| Body Width: | |
| Between 0.248 inches and 0.325 inches | |
| Body Height: | |
| 0.085 inches | |
| Maximum Power Dissipation Rating: | |
| 910.0 milliwatts | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Storage Tempurature Range: | |
| -65.0/+150.0 degrees celsius | |
| Features Provided: | |
| Hermetically sealed and monolithic and positive outputs and w/storage and programmable and programmed and bipolar and 3-s | tate output |
| and schottky and high speed and expandable and w/buffered output and w/decoded output and w/enable and w/disable | |
| Inclosure Material: | |
| Ceramic and glass | |
| Inclosure Configuration: | |
| Flat pack | |
| Output Logic Form: | |
| Transistor-transistor logic | |
| Input Circuit Pattern: | |
| 6 input | |
| Terminal Surface Treatment: | |
| Solder | |
| Voltage Rating And Type Per Characteristic: | |
| 5.5 volts power source | |
| Time Rating Per Chacteristic: | |
| 40.00 nanoseconds propagation delay time, low to high level output and 84.00 nanoseconds propagation delay time, high to I | ow level |
| output | |
| Memory Device Type: | |
| Rom | |
| Memory Capacity: | |
| Unknown | |
| Test Data Document: | |
| 82577-932821 standard (includes industry or association standards, individual manufactureer standards, etc.). | |
| Terminal Type And Quantity: | |
| 16 flat leads | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| | |

Yes - demil/mli

NSN 5962-01-076-7972

Memory Microcircuit - Page 2 of 2

Fiig: A458a0

