## NSN 5962-01-077-0392

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-077-0392 **Body Length:** 0.440 inches **Body Width:** Between 0.248 inches and 0.325 inches **Body Height:** 0.085 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and high speed and schottky and programmed and bipolar and w/storage and 3-state output and w/decoded output and expandable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 40.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 82577-932623 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life:

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

N/a

## NSN 5962-01-077-0392

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0