## NSN 5962-01-078-0603

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-078-0603

Body Outside Diameter:	
Between 0.335 inches and 0.370 inches	
Body Height:	
Between 0.165 inches and 0.185 inches	
Maximum Power Dissipation Rating:	
600.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Complementary outputs and schottky and bipolar and high speed and w/enable and hermetically sealed and hybrid	
Inclosure Material:	
Glass and metal	
Inclosure Configuration:	
Can	
Input Circuit Pattern:	
3 input	
Design Function And Quantity:	
1 comparator, voltage	
Case Outline Source And Designator:	
T0-100 joint electron device engineering council	
Terminal Surface Treatment:	
Tin	
Time Rating Per Chacteristic:	
12.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low lev	el
output	
Test Data Document:	
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	