NSN 5962-01-078-0603

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-078-0603

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.165 inches and 0.185 inches

Maximum Power Dissipation Rating:

600.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Complementary outputs and schottky and bipolar and high speed and w/enable and hermetically sealed and hybrid

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Input Circuit Pattern:

3 input

Design Function And Quantity:

1 comparator, voltage

Case Outline Source And Designator:

T0-100 joint electron device engineering council

Terminal Surface Treatment:

Tin

Time Rating Per Chacteristic:

12.00 nanoseconds propagation delay time, low to high level output and 12.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0