NSN 5962-01-078-1416

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-078-1416 **Body Length:** 0.630 inches **Body Width:** 0.630 inches **Body Height:** 0.230 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hybrid and w/resistor and hermetically sealed and burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 switch **Terminal Surface Treatment:** Solder **Product Name:** Positive/negative switch Voltage Rating And Type Per Characteristic: 30.0 volts power source **Time Rating Per Chacteristic:** 100.00 nanoseconds delay **Hybrid Technology Type:** Monolithic **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 flat leads Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-078-1416

Hybrid Microcircuit - Page 2 of 2



Fiig:

A458a0