## NSN 5962-01-078-1813

Memory Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5962-01-076-1613  |
|--|
| Body Length:   |
| Between 0.750 inches and 0.785 inches  |
| Body Width:  |
| Between 0.285 inches and 0.291 inches  |
| Body Height:   |
| Between 0.120 inches and 0.185 inches  |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and monolithic and positive outputs and low power and schottky and w/open collector and programmable and         |
| programmed and w/enable and w/disable  |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Transistor-transistor logic  |
| Input Circuit Pattern:   |
| 6 input  |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 5.5 volts power source   |
| Time Rating Per Chacteristic:  |
| 75.00 nanoseconds propagation delay time, low to high level output   |
| Memory Device Type:  |
| Rom  |
| Memory Capacity:   |
| Unknown  |
| Test Data Document:  |
| 26916-058-001842 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                    |
| Terminal Type And Quantity:  |
| 16 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

Fiig: A458a0

Demilitarization: Yes - demil/mli