NSN 5962-01-078-5750

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-078-5750 **Body Length:** 0.830 inches **Body Width:** 0.310 inches **Body Height:** 0.120 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and bipolar and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Current Rating Per Characteristic:** 140.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Capitance Rating Per Characteristic:** 5.00 input picofarads and 8.00 output picofarads **Time Rating Per Chacteristic:** 50.00 nanoseconds access **Memory Device Type:** Prom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-078-5750

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0