

View Online at <https://aerobasegroup.com/nsn/5962-01-078-9380>

Body Length:

0.280 inches

Body Width:

0.250 inches

Body Height:

Between 0.030 inches and 0.085 inches

Maximum Power Dissipation Rating:

750.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and high speed and w/field effect transistor switch

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

2 channel

Design Function And Quantity:

2 driver

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-22.0 volts power source and 22.0 volts power source

Time Rating Per Characteristic:

300.00 nanoseconds propagation delay time, low to high level output and 375.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

88818-a574a862 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0