NSN 5962-01-079-4557

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-079-4557 **Body Length:** Between 1.980 inches and 2.020 inches **Body Width:** Between 0.565 inches and 0.590 inches **Body Height:** Between 0.050 inches and 0.120 inches **Maximum Power Dissipation Rating:** 250.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and w/buffered output and bipolar and bidirectional and programmable and 3-state output and w/enable and dynamic and w/storage **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 22 input **Design Function And Quantity:** 1 timer **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: -0.3 volts power source and 15.0 volts power source **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 40 printed circuit Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-079-4557

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0