# NSN 5962-01-080-6489

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-080-6489

# **Body Length:**

Between 0.750 inches and 0.795 inches

# **Body Width:**

Between 0.245 inches and 0.300 inches

# **Body Height:**

Between 0.120 inches and 0.180 inches

# **Maximum Power Dissipation Rating:**

450.0 milliwatts

#### **Operating Tempurature Range:**

+0.0/+85.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Test set, radar, type an/tpm-25a

#### **Features Provided:**

Hermetically sealed and monolithic and w/strobe

**Inclosure Material:** 

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

#### Input Circuit Pattern:

Quad 2 input

#### **Design Function And Quantity:**

4 receiver, line

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

5.0 volts power source

#### Time Rating Per Chacteristic:

25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

45413-134780 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0