

View Online at <https://aerobasegroup.com/nsn/5962-01-081-4227>

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Body Height:

Between 0.155 inches and 0.185 inches

Maximum Power Dissipation Rating:

35.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hybrid and hermetically sealed and positive outputs and expandable and high current and high voltage

Inclosure Material:

Glass and metal

Inclosure Configuration:

Can

Input Circuit Pattern:

5 input

Design Function And Quantity:

1 driver, high current

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

260.00 nanoseconds propagation delay time, low to high level output

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

10 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0