NSN 5962-01-081-4227

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-081-4227

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.155 inches and 0.185 inches
Maximum Power Dissipation Rating:
35.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hybrid and hermetically sealed and positive outputs and expandable and high current and high voltage
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
5 input
Design Function And Quantity:
1 driver, high current
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
260.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig: